

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	Cheney	18.11.30

SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 1.8A (PIN1,4) ; OTHER CONTACTS 0.25A
 - CONTACT RESISTANCE: 30mΩ MAX.(INITIAL)
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE
 - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC.
- MECHANICAL CHARACTERISTICS:
 - INSERTION FORCE : 35N MAX. INITIAL.
 - WITHDRAWAL FORCE : 9.8N MIN INITIAL, 8N MIN, FOR AFTER TEST.
- LIFE TEST: 5000 CYCLES
- 3-1.OPERATING TEMPERATURE:-55°~+85°C
- OTHER GENERAL SPEC TO REFER "2UB1711-001111F_SPEC_A"
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION MARK :⊙
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: 
- FOR IR REFLOW ROFILE,PEAK TEMPERATURE:260°C MAX.10SECS.
- PACKAGING : TRAY.

G	SPRING TERMINAL	1	STAINLESS STEEL	
F	BACK SHELL	1	STAINLESS STEEL	
E	FRONT SHELL	1	STAINLESS STEEL	NICKEL PLATING
D	CONTACT_A	8	COPPER ALLOY	Au 1u"MIN. ON CONTACT AREA, MATTE Sn 80u"MIN. ON SOLDER TAIL, ALL OVER NICKEL PLATING
C	CONTACT_B	5	COPPER ALLOY	
B	COVER	1	HIGH TEMPERATURE PLASTIC	BLACK
A	HOUSING	1	UL94V-0	
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES			 Singatron Enterprise Co., Ltd. 信音企業股份有限公司	
DECIMALS:		ANGLES:	TITLE	
X	:±0.5	X	:±2°	USB 2.0+USB 3.0 CONNECTOR PART NO.2UB2Y11-000111F SCALE 1:1 UNIT: mm SIZE: A3 SHEET: 10F1 REV:A CUSTOMER COPY
X.X	:±0.3	X.X	:±1°	
X.XX	:±0.2			

