



Recommend PCB Layout
Tolerance: ±0.05mm (Component Side)
Recommend PCB THICKNESS: 1.20mm

- SPECIFICATIONS:
1. OTHER GENERAL SPEC. TO REFER "ZHE1503 SERIES SPEC".
 2. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 3. HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING.
 4. REFLOW SOLDER CAPABLE 260°C 10SECS.
 5. FOR REFLOW SOLDERING LEAD-FREE PROCESS.
 6. PACKAGE: SEE "ZHE4000 SERIES " PACKAGE.

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR RELEASE	BONNIE	2008.12.26
B	ECN NO. L090020	AMYC	2009.04.27

PART NO.
2HE1528-001111

- PACKAGE
- 1: TAPE & REEL
- HOUSING COLOR
- 1: BLACK
- CONTACT PLATING
- 1: GOLD FLASH
- DIM A:
- 1: 1.8mm

D	INSULATION FILM	1	MYLAR	TIN PLATING
C	SHELL	1	COPPER ALLOY	GOLD PLATED
B	CONTACT	19	COPPER ALLOY	BLACK COLOR
A	HOUSING	1	LCP UL 94V-0	PLATING & COLOR
NO	DESCRIPTION	QTY	MATERIAL	

UNLESS OTHERWISE SPECIFIED TOLERANCES

Singatron Enterprise Co., Ltd.
信音企業股份有限公司

HDMI BSD FEMALE SMT (BOTTOM) TYPE

DECIMALS: ANGLES:

X : ±0.5 X : ±2°
X.X : ±0.3 X.X : ±1°
X.XX : ±0.2

APVD

CHKD

APVD

SCALE: N/A

UNIT: mm

SIZE: A3

SHEET: 1 OF 1

REV: B

CUSTOMER COPY