



SPECIFICATIONS:

1. See " D-SUB(9 PIN) PRODUCT SERIES SPEC "
2. TO CONFORM TO THE "SINGATRON HSF SPECIFICATION"
3. PACKAGE: SEE "2DS1542 SERIES" PACKAGE
4. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING: **G.P. PASS**
5. FOR WAVE SOLDERING LEAD-FREE PROCESS.

PART NO.
2DS1542-000111

- PACKAGE
- 1: TRAY
- HOUSING COLOR
- 1: BLACK
- CONTACT PLATING
- 1: Gold Flash / TIN PLATING

REV.	ECN NO. OR DESCRIPTION	REVISED	DATE
A	PDR RELEASE	Amyc	2009.04.10
B	ECN NO. L090027	Amyc	2009.05.20
C	ECN NO. L090055	Amyc	2009.09.10

D	HOOK	1	COPPER ALLOY	TIN PLATED
C	Shell	1	SPCC	NI PLATED
B	Insulator	1	PBT UL 94V-0	BLACK
A	Contacts	9	BRASS	Gold Flash / TIN PLATING
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

Singatron Enterprise Co., Ltd.

DECIMALS:	ANGLES:
X : ±0.5	X : ±2°
X.X : ±0.3	X.X : ±1°
X.XX : ±0.2	

TITLE	DRAWN	CHKD	APVD
D-SUB 0.20"(5.10mm) 9 MAIL STRAIGHT DIP MOUNT	Amyc 2009.09.14	Johnson 2009.09.14	Johnson 2009.09.14

PART NO. 2DS1542-000111

SCALE: N/A

UNIT: mm

SHEET: 1 OF 1

REV: C

CUSTOMER COPY

Recommend PCB Layout
Tolerance: ±0.05mm (Top view)
Recommend PCB THICKNESS: 1.6mm