



TOLERANCE: ±0.05
STANDARD PCB LAYOUT

- SPECIFICATIONS:
- VOLTAGE RATING: 250 VAC RMS.
 - CURRENT RATING: 1 AMP.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC RMS 60 Hz. FOR 1 MINUTE.
 - INSULATION RESISTANCE: 1000 MEGOHMS MIN AT 500 VDC.
 - CONTACT RESISTANCE: 20 MILLIOHMS MAX.
 - DURABILITY: 20 CYCLES.
 - OTHER GENERAL SPEC. TO REFER "2FF1500 SERIES SPEC".
 - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 - GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING: **[G.P. PASS]**
 - PACKAGE: SEE "2FF1501 SERIES" PACKAGE

PART NO.
2FF1501-022111

PACKAGE
1: Tube
HOUSING COLOR
1: Black
CONTACT
1: TIN
SEE "TABLE 1"
NO of Circuit
HOUSING MATERIAL
0: PBT UL-94 V0

"TABLE 1"

PART NO	Circuit	Dimension		
		A	B	C
2FF1501-022111	22	26.25	28.80	30.90

B	CONTACT	22	PHOSPHOR BRONZE	TIN PLATING
A	HOUSING	1	SEE "PART NO."	BLACK COLOR
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:	TITLE	DATE	SCALE	UNIT	SHEET	REV
X : ±0.5	X : ±2°	FPC/FC 1.25 PITCH NON ZIF SIDE ENTRY UPPER CONTACT	2009/05/07	N/A	mm	1 OF 1	A
X.X : ±0.3	X.X : ±1°						
X.XX : ±0.2							

Singatron Enterprise Co., Ltd.
信晉企業股份有限公司

PART NO. 2FF1501-022111

CUSTOMER COPY

REV	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR RELEASE	AM/C	2009.05.07