



Recommend PCB Layout
Jack Top View
(Tolerance: ±0.05mm)

PART NO.
2PH1512-0001X1

PACKAGE
1: BAG
HOUSING COLOR
1: RED
2: BLUE
CONTACT PLATING
1: Gold Flash Over Nickel
Plating 50u

- SPECIFICATIONS:
1. Current Rating: 3 Amps
 2. Insulator resistance: 5000 Megohms min.
 3. Dielectric withstanding: AC 500 V
 4. Operating Temperature: -40°C to +105°C
 5. SOLDER HEAT RESISTANCE: WAVE SOLDERING 260°C 10SECS.
 6. TO CONFORM TO THE "SE-01-001" & "ROHS DIRECTIVE"
 7. GREEN PRODUCT IDENTIFICATION LABEL IN PACKING: **G.P. PASS**
 8. SEE "2PH1512 SERIES SPEC"
 9. PACKING: SEE "2PH1512 SERIES"

REV	ECN NO	OR DESCRIPTION	REVISED	DATE
A		PDR RELEASE PART NO.2PH1512-0001111 2PH1512-000111-2PH1512-0001X1 SERIES APPROVED PART NO.2PH1512-000121	LULU	2007.10.26

B	CONTACT	9	BRASS	GOLD FLASH OVER NICKEL PLATING 50u"
A	INSULATOR	1	PBT UL 94V-0	SEE "PART NO."
	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:	ANGLES:			
X : ±0.5	X : ±2°			
X.X : ±0.3	X.X : ±1°			
X.XX : ±0.2				
Singatron Enterprise Co., Ltd. 信音企業股份有限公司				
TITLE: 2.54mm (0.1") PIN HEADER (2202 SERIES)				
DWN	Jul 2007.10.29	PART NO.	2PH1512-0001X1	
CHKD	JANSON 2007.10.29	SCALE:	1/1	UNIT: mm
APVD	JANSON 2007.10.29	SIZE:	A3	SHEET: 1 OF 1
REVISION: REV: A				
CUSTOMER COPY				