



RECOMMEND MATING PLUG

OPTICAL FIBER PLUG

SPECIFICATIONS:

- ELECTRICAL CHARACTERISTICS:
  - 1-1. RATING: 12V 1A
  - 1-2. CONTACT RESISTANCE: 30mΩ MAX(INITIAL).
  - 1-3. DIELECTRIC VOLTAGE WITHSTAND: 500V AC FOR ONE MINUTE
  - 1-4. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
- MECHANICAL CHARACTERISTICS:
  - 2-1. INSERTED FORCE : 3.5 KGS MAX.
  - 2-2. WITHDRAWAL FORCE : 0.3~4.0 KGS
- LIFE TEST: 5,000 CYCLES MIN.
- PACKAGING: TAPE & REEL
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK:
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING:
- FOR LEAD-FREE PROCESS.



K	IC DRIVER	1	BRASS	NICKEL PLATING
---	-----------	---	-------	----------------

J	METAL	1	COPPOR ALLOY	Ni 60u" Min
---	-------	---	--------------	-------------

I	SHIELDING	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	-----------	---	-----------------	-----------------------------

H	EARTH SPRING-A	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	----------------	---	-----------------	-----------------------------

G	EARTH SPRING-B	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	----------------	---	-----------------	-----------------------------

F	EARTH TERMINAL	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	----------------	---	-----------------	-----------------------------

E	TIP SPRING	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	------------	---	-----------------	-----------------------------

D	RING SPRING	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	-------------	---	-----------------	-----------------------------

C	CASE	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	------	---	-----------------	-----------------------------

B	COVER	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	-------	---	-----------------	-----------------------------

A	BODY	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50u" Ni Min
---	------	---	-----------------	-----------------------------

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
----	-------------	-----	----------	-----------------

UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:	ANGLES:			
X : ±0.5	X : ±2°			
X.X : ±0.3	X.X : ±1°			
X.XX : ±0.2				

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR NO.:S081021-2A	Sidney	2008.11.07
B	ECN NO.:S090807	Sidney	2009.07.23

Singatron Enterprise Co., Ltd.  
信昌企業股份有限公司

TITLE	Ø3.5 PHONE JACK (WITHOUT IC)
DWN	Scale 2008.07.23 PART NO. 2Sf-D373-D03
CHKD	LUSSSEN SCALE: 3/1 UNIT: mm
APVD	WAW SIZE: A3 SHEET: 1 OF 1 REV: B

CUSTOMER COPY