


SPECIFICATION:

1. CONTACT CURRENT RATING 1.0A AT 30V AC
2. CONTACT RESISTANCE 60 MILLIOHMS Max.
3. INSULATION RESISTANCE 100 MEGAOHMS Min.
4. DIELECTRIC WITHSTANDING VOLTAGE 100V AC FOR 1 MINUTE
5. INSERTION FORCE 35N Max.
6. EXTRACTION FORCE 7N MIN.(INITIAL) ; 3N MIN.(10000 CYCLE)
7. DURABILITY 10000 INSERTION/EXTRACTION CYCLE
8. OPERATING TEMPERATURE -55~85°
9. IFR FOLLOW CHART PEAK TEMPERATURE 250°±5 10SEC.
10. PACKAGING TAPE & REEL
11. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
12. GREEN PRODUCT IDENTIFICATION MARK ON JACK:
13. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING: **G.P. PASS**
14. FOR LEAD-FREE PROCESS.

Connector Termination Assignment:

Contact Number	Signal Name
1	VBUS
2	D-
3	D+
4	ID
5	GND
6-10	Audio Use Shield



E	MYLAR	1	KAPTON	YELLOW
D	SHELL	1	STAINLESS STEEL	Ni 60u"
C	LOWER TERMINAL	5	COPPY ALLOY	CONTACT Au 10u"Min. SOLDER TAIL GOLD FLASH Ni 50u"Min.
B	UPPER TERMINAL	5	COPPY ALLOY	CONTACT Au 10u"Min. SOLDER TAIL GOLD FLASH Ni 50u"Min.
A	BODY	1	High Temp. Thermoplastic U94V-0	BLACK
NO	DESCRIPTION		MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singatron Enterprise Co., Ltd. 信音企業股份有限公司				
TITLE		MINI USB 10 PIN NORMAL TYPE CONN.		
DWN		16m/2009.08.20		
CHKD		Lusem/2009.08.20		
APVD		Mao/2009.08.20		
DECIMALS:		ANGLES:		
X : ±0.50		X : ±2°		
X.X : ±0.30		X.X : ±1'		
X.XX : ±0.20				
CUSTOMER COPY				

REV/ECN NO	OR DESCRIPTION	REVISED	DATE
A	PDR NO.1090615-2A	Tom	2009.06.30