



Specifications:

1. Electrical:

- 1-1 Rating: AC 5V/0.5A
- 1-2 Contact resistance: 50m Ohm or less
- 1-3 Insulation Resistance: 100M Ohm Min at DC500V
- 1-4 Dielectric Withstanding Voltage: AC 100V for 1minute

2. Mechanical:

- 2-1 Insertion Force: 35N(3.57kgf)Max.
- 2-2 Withdrawal Force: 1N(0.1kgf)Min.
- 3. Solder heat resistance: Wave soldering 260°C 10 Secs.
- 4. To conform to the "SE-01-001" & "ROHS DIRECTIVE"
- 5. Green product identification label in packing: G.P. PASS
- 6. For wave soldering LEAD-FREE process.
- 7. Information: 2UP2000-100112

- PACKAGE
- 2: PE BAG
- BODY COLOR
- 1: BLACK
- CONTACT PLATING
- 1: GOLD PLATING
- PRODUCT TYPE
- 1: PLUG

C	SHELL	1	BRASS	GOLD 1μ"
B	TERMINAL	8	PHOSPHOR	GOLD 3μ"
A	HOUSING	1	HIGH TEMPERATURE THERMOPLASTIC	BLACK COLOR
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS:		ANGLES:		
X	:±0.5	X	:±2°	
X.X	:±0.3	X.X	:±1'	
X.XX	:±0.2			
Singatron Enterprise Co., Ltd. 信晉電子(中山)有限公司				
TITLE: MINI USB CONNECTOR <DIP TYPE>				
DWN	JASMINC	PART NO. 2UP2000-100112		
CHKD	06.3.2	SCALE:	UNIT:	mm
APVD	06.3.2	SIZE:	A3	SHEET: OF
REV: A				

CUSTOMER COPY

REV. ECN NO OR DESCRIPTION	REVISED DATE
A PRODUCT RELEASE	JASMINC 3/7-'06