





REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR NO.:T09012015M~O	Steve	2009.01.08




Recommend Panel Cut-out



NOTES:

1. WATERPROOF RATE: IP68
IP68: IMMERSED IN 1M WATER FOR 24 HOURS
2. ELECTRICAL CHARACTERISTICS
TEMPERATURE RANGE: -40°C TO +100°C
RATING: 60V AC/DC 5A
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
3. SPECIFICATIONS:SEE "M12 SERIES SPECIFICATIONS".
4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
5. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING: **G.P. PASS**
6. FOR PANEL THICKNESS MAX OF 4.5mm
7. ORDER INFORMATION:2MT3003-XOX300

- 3- 3 PIN
- 4- 4 PIN
- 5- 5 PIN



SECTION A-A

P/N:	2MT3003-X05300	2MT3003-X04300	2MT3003-X03300
	Pin Assignments Front View	Pin Assignments Front View	Pin Assignments Front View

F	LIQUID GLUE	1		BLACK
E	SHIELD	1	BRASS	NICKEL PLATING 100u"
D	NUT	1	BRASS	NICKEL PLATING 100u"
C	O-RING	1	EPDM	BLACK
B	MALE PIN	*	BRASS	6u" GOLD PLATED OVER NICKEL PLATING
A	BODY	1	NYLON+33%GF	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES		Singatron Electronic(China) Co., Ltd. 信音電子(中國)股份有限公司		
DECIMALS:		TITLE		
X	:±0.5	M12 SERIES FRONT MOUNT MALE CONN. (3~5PIN) HEXAGONAL BACKSHELL		
ANGLES:		DWN	Steve	PART NO.2MT3003-XOX300
X	:±2°	CHKD	Quan	SCALE 2:1 UNIT: mm
X.X		APVD	Lussen	SIZE: A3 SHEET:1 OF 1
X.XX		REV: A		
CUSTOMER COPY				