


REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR RELEASE	Even	2018.06.22

**SPECIFICATIONS:**

- VOLTAGE RATING: 150 VAC MAX.
- CURRENT RATING: 1.5 AMP MAX.
- INSULATION RESISTANCE: 500M OHMS MIN. AT 500 VDC.
- DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC 60Hz 1 MINUTE.
- DURABILITY: 5000 CYCLES .
- OPERATING TEMPERATURE: -30°C TO +70°C.
- TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
- HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: 
- PACKAGE: SEE "2RJ1792-000111F" PACKAGE.
- FOR REFLOW SOLDERING LEAD-FREE PROCESS.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
- OTHER GENERAL SPEC. TO REFER "2RJ1792-000111F SPEC".

**PART NO.**  
**2RJ1792-000111F**

- SUFFIX: HALOGEN FREE
- PACKAGE  
1: TAPE & REEL
- HOUSING COLOR  
1: BLACK
- CONTACT AREA PLATING  
1: GOLD FLASH ON CONTACT AREA,  
MATTE TIN 50u" MIN ON SOLDER AREA.  
50u" MIN NICKEL UNDERPLATED OVERALL.

F	CAP	1	LCP UL 94V-0	BLACK
E	DEFEND	2	LCP UL 94V-0	BLACK
D	LED	2	WHITE/AMBER	TIN
C	SHIELD	1	SUS201	50u" NICKEL PLATED
B	CONTACT	8	C5210R-EH	SEE PART NO.
A	HOUSING	1	PA10T UL 94V-0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

 Singatron Enterprise Co., Ltd.  
信音企業股份有限公司

DECIMALS: ANGLES:  
X :±0.5 X :±2°  
X.X :±0.3 X.X :±1°  
X.XX :±0.2

TITLE	RJ45 JACK, R/A, W/LED, DIP TYPE		
DWN	EVEN 2018.06.22	<b>PART NO. 2RJ1792-000111F</b>	
CHKD		SCALE 3/1	UNIT: mm
APVD	ANGELA 2018.06.22	SIZE: A3	SHEET: 1 OF 1 REV: A

**CUSTOMER COPY**

