



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
B	PDR NO.T091106-3A/3C	Harlen	2010.01.16
C	ECN NO.:S110852	Shawn	2011.09.02
D	ECN NO.:S121109	YF	201403.26

- NOTES:
1. WATERPROOF RATE: IP67
IP67: IMMERSED IN 1M WATER FOR 30 MINUTES
 2. ELECTRICAL CHARACTERISTICS
TEMPERATURE RANGE: -40°C TO +100°C
CURRENT RATING: 5A
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
 3. SPECIFICATIONS:SEE "CIRCULAR SERIES SPECIFICATIONS".
 4. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 5. GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING: **[G.P. PASS]**
 6. FOR PANEL THICKNESS MAX OF 4.0mm
 7. ORDER INFORMATION: 2CT3002-X0X300

- 3-CURRENT RATING 5A
- 02- 2 PIN
- 03- 3 PIN
- 04- 4 PIN
- 05- 5 PIN
- 06- 6 PIN
- 07- 7 PIN
- 08- 8 PIN

E	LIQUID GLUE	1	N/A	BLACK
D	NUT	1	NYLON+33%GF	BLACK
C	GASKET	1	EPDM	BLACK
B	MALE PIN	*	BRASS	6u" GOLD PLATING OVER NICKEL PLATING
A	BODY	1	NYLON+33%GF	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
Singatron Electronic(China) Co., Ltd. 信音電子(中國)股份有限公司				
DECIMALS:		ANGLES:		
X	:±0.5	X	:±2°	
X.X	:±0.3	X.X	:±1°	
X.XX	:±0.2			
TITLE	CIRCULAR STANDARD SIZE (SOLDER/LOCK TYPE) MALE CONN. MALE (2~8)PIN (5A)			
DWN	YF	PART NO.2CT3002-X0CB00		
CHKD	Harlen	SCALE 2:1	UNIT: mm	
APVD	Quan	SIZE: A3	SHEET:1 OF 1	REV: D
CUSTOMER COPY				

